

EGC Enterprises, Inc.

140 Parker Court Chardon, Ohio 44024 Phone: (440) 285-5835

PRODUCT DATA SHEET

PDS-123

TITLE Thermacord® TC-12

INFORMATION ON THIS PRODUCT DATA SHEET IS TYPICAL, SUBJECT TO CHANGE WITHOUT NOTICE AND DOES NOT CONSTITUTE A SPECIFICATION OR PRODUCT WARRANTY.

Description: Thermacord® TC-12 is a twisted cord product consisting of a flexible graphite base with a passive corrosion inhibitor and graphite yarn reinforcement.



| Graphite Base Properties | Typical Value | | | |
|---------------------------------|---------------------------|--|--|--|
| Carbon Content | > 95% | | | |
| Leachable Chloride | < 100 ppm | | | |
| Sulfur Content | < 1000 ppm | | | |
| Phosphorus | ≥ 1500 ppm | | | |
| Nominal Density | 70 lbs. / ft ³ | | | |

| TC-12 General Cord Properties | | | | | |
|-------------------------------|------------------------|-------|-------|-------|--|
| Temperature | 900° F (482° C) in air | | | | |
| Composition by weight: | | | | | |
| Graphite base weight | 83.6% | | | | |
| Graphite yarn weight | 13.76% | | | | |
| Adhesive weight | 2.64% | | | | |
| Cord Diameters Available | .070" | .090" | .110" | .120" | |

Brian Biller 4-17-14

Department Manager Approval

Date

Rev. A CRN 314002