



EGC Enterprises, Inc.

140 Parker Court
Chardon, Ohio 44024
Phone: (440) 285-5835

PRODUCT DATA SHEET

PDS-133

TITLE Thermafoil® Grade TF-LHS

INFORMATION ON THIS PRODUCT DATA SHEET IS TYPICAL, SUBJECT TO CHANGE WITHOUT NOTICE AND DOES NOT CONSTITUTE A SPECIFICATION OR PRODUCT WARRANTY.

Description: Laminate material made with Thermafoil® Grade B flexible graphite, with 70 lb/ft³ nominal density, bonded to .0025" thick 316 stainless steel wire mesh (150 mesh) insert, bonded with a carbon based thermally activated adhesive.

Specifications:

Graphite base properties

Carbon	98.0% Minimum
Ash	2.0% Maximum
Leachable Chlorides	< 50ppm

Density	70 #/cu.ft Nominal
Variation	± 5 % of Nominal

Compressibility 40% Typical

Recovery 15% Typical

Tensile Strength 3800 psi Typical

Creep/Relaxation < 5% Typical

Availability:

Thickness	.012" - .125" (<i>Thicker laminates are available upon request</i>)
Variation	± 10 % of Nominal

Laminate Size	24" x 24" up to 24" x 60" (<i>Larger sizes are available upon request with the substitution of pressure sensitive adhesive instead of thermally activated adhesive.</i>)
----------------------	---


Department Manager Approval

3/20/13
Date